ATTENTION BUYER: IF YOU ARE NOT SATISFIED, PLEASE DON'T RETURN THIS PRODUCT TO THE RETAILER- CONTACT US FIRST FOR QUICKEST RESPONSE!!!!

HELPFUL HINTS

CLOGGED NOZZLES - Gently tap the head of the nozzle with a screwdriver to loosen any sediment that may have accumulated. If this doesn't work remove "O" Ring and place the nozzle in a container of vinegar or household lime and scale remover for approximately 30 minutes. Stir or shake to help loosen the debris. For heavier deposits try soaking longer or scrubbing with a stiff non-metallic brush. Never attempt to clear nozzles with pins, nails or other sharp objects.

Leaking - Leaking at the base of the nozzle can occur if the "O" ring is damaged or is not evenly seated. Turning a damaged "O" ring over sometimes does the trick. Don't overtighten the nozzle, this could cause damage to the "O" ring. Leaking can occur if the nozzle is not inserted correctly into the thread. A leak at the hose attachment could be caused by the filter washer not being evenly seated, or sediment inside the hose adapter.

AVISO PARE EL COMPRADOR: SI USTED NO SE ENCUENTRA SATIFECHO, NO DEVUELVA ESTE PRODUCTO AL VENDEDOR- !!!PONGASE EN CONTACTO CON NOSOTROS PRIMERO PARA UNA RESPUESTA MAS RAPIDA!!!

CONSEJOS UTILES

BOQUILLAS ATORADAS- Con cuidado golpee la cabeza de la boquilla con un destornillador para soltar cualquier tipo de sedimento que se haya acumulado. Si esto no fucionara, reitre el anillo "O" y coloque las boquillas en un recipiente con vinagre o removedor de sarro y cal domestico durante approximadamente 30 minutos. Revuelva y sacuda para ayudar a soltar restos y paritculas. En el case de depositos mas severos, haga remojar durante mas tiempo o refriegue con una escobilla de consistencia dura no metallica. Nunca intente desobstruir las boquillas con alfileres, clavos u otros objetos puntiagudos.

FUGAS-Podrian ocasionarse fugas o goteras en la base de la boquilla si el anillo "O" se encuentra danado o no se encuentra correctamente colocado. Se puede solucionar algunas veces este problema dandole la vuelta al anillo "O". No ajuste demasiado la boquilla ya que esto puede causar danos al anillo "O". Pueden ocurrir fugas si la boquilla no se ah insertado correctamente dentro de la rosca. Una fuga en el accesorio de la manguera podria occurir debido a que la arandela del filtro no se ha colocado correctamente o a que exista sedimento dentro del adaptador de la manguera.